

U.L.C. TANKS

Underground Plastic Over Steel Tank (TIPSA)

The Efficient Solution for your Fueling Business

The TIPSA tank will deliver exceptional protection for petroleum fuel storage

The base of this system is a proven single wall** steel tank built to a recognized standard. The outer layer is made from a product known for its resistance to corrosion and durability, High Density Polyethylene (HDPE). The secondary containment is applied over the steel tank and forms a sealed envelope around it.

A vacuum is then applied to the interstice space to provide an effective secondary layer. This will procure you the ease of mind that your investment is sound and safely stored, but you will have also saved on installation costs.

The exterior wall of the primary tank being in a space under vacuum will then be protected from corrosion. This space between the steel tank exterior and the inside of the HDPE envelope can be monitored for vacuum and liquid presence. We have more worldwide installations than any other competitors. This is a proof of the performance of the product.

Standard Design Features:

- Superior performance in corrosion protection and secondary containment
- Inner tank can be compartmentalized
- Total compatibility with petroleum fuels
- Sand, pea gravel, or crushed stone may be used for backfill*
- Globally recognized third party approval to UL and ULC
- Proven performance
- Exceptional 30 years warranty
- No cathodic protection needed
- Interior bottom liner available

Sizes available:

8 ft. tank dia. up to 57,000 Liters
10 ft. tank dia. up to 107,000 Liters
12 ft. tank dia. up to 150,000 Liters

All sizes are available with the requested number of divisions, sumps, manholes and fittings.

*Inquire for details.

**ULC S603 single wall tanks for Canadian installations. Double wall steel also available on request.



"This high-quality product undergoes a series of tests and is built to last. Proud and dedicated workmanship goes into the fabrication of every tank."



Distributed by: