

U.L.C. TANKS

Workbench Tank ULC-S601-07-Latest Standard

Designed for the Storage of Flammable and Combustible Liquids





Aboveground Single Wall

Applications:

- New or used oil of all types
- New or used anti freeze
- Used cooking oil
- The list is endless

Standard Design Features:

- Workbench top plate, 3/16" thick steel
- Two(2) fully welded saddles support
- 1/8" thick tank shell construction
- Each compartment includes:
 - Two(2) 2" N.P.T. body flange
 - One(1) 1-1/2" N.P.T. bottom drain
- 3" bend / guard on back of workbench area
- Venting as per code



250 imperial gallon model shown

Tank Exterior:

- Sandblasted to SSPC-SP6, commercial blast
- Painted:
 - Primary coat: Two part high built epoxy 2-4 mils dry
 - Sec. coat: Two part Polyurethane 2-3 mils dry
 - Final coat: Two part Polyurethane 2-3 mils dry
- Paint Warranty for two(2) years from date of manufacturing
- Warranty on tank for a period of five(5) years from date of manufacturing



250 and 110 imperial gallon models shown

Options:

- Multiple compartments
- Pumping station

- Liquid level gauge
- 15 mil Interior liner

- Extra 1-1/2" opening / comptnt

Specifications:

Capacity		Dimensions (in.)						Plate Thickness		Fittings per compartment**
Liters	Imp. Gal.	A	B	C	D	E	F	Tank Shell	Workbench Top	N.P.T. Body Flange
500	110	48	36	28	37	30.5	22.5	1/8"	3/16"	Two(2) 2" & Two(2) 1-1/2" + 1-1/2" drain
1 135	250	84	60	36	37	38.5	30	1/8"	3/16"	(2) 2" & (2) 1-1/2" + 1-1/2" drain

NOTES : * Bottom drain. ** Extra 1-1/2" fitting (on bench top) as option.

Inquire for details

Distributed by: